

Courier Unit - Fact Sheet

CU-2975 Unit	Molded HDPE -- Container and interlocking Lid with a Neoprene Seal form a Water Resistant unit. A passivated Stainless Steel Exoskeleton W/ Self Sealing Lid & Release Valve. Unit has Three Grip Handles plus Wheels and an Integral, Pull-Out Handle. Optional Input Slot Door.
Outside Dimensions	31.3" X 20.4" X 15.4"
Inside Dimensions	29" X 18" X 13.8"
Weight	50 lbs. (with Metal & Electronic Alarm/ Battery components installed.)
Locking	Nexgen[®] Programmable Key System by MEDECO... has Lock Components of S/S and Copper. Comes W/ Proprietary Software and Web Site. Optional locking systems are available.
Tracking	Quad Band EDGE/GPRS/GSM Modem working in conjunction with GIS Internet Software and Global Satellite Communication. (Tracking & Sensor monitoring - 24/7)
Sensing	A P2S2 proprietary circuit board manages a series of sensing devices to match specific security needs: Temperature, Humidity, Infra-Red, Motion/G-Force, Power, Photo & Other Optional Sensors including Chemical, Biological & Radiological can be included. Has a RS-232 Data Port for direct info download.
Power	Battery Pack; Two 9A.H. 12V batteries w/trickle charger and a 120v recharge connector all installed in an ABS Plastic Housing.
Alarm	125 db Alarm at Illegal entry or in the event of sensor anomalies.
F.O.B.	Hoopeston, IL

